

# TTL STROBE & PRICE COMPARISON

## TTL Strobe

<b>Manufacturer</b>	Pixapro	Interfit	Phottix	Profoto
<b>Model</b>	CITI600 TTL	S1	Indra 500	B1 Air 500
<b>Power</b>	600Ws	500Ws	500Ws	500Ws
<b>Guide Number (ISO 100)</b>	87m	48.7	45	Unknown
<b>Recycling Time</b>	0.01 – 2.5 Seconds Recycle Time	3 Seconds	With Phottix Indra AC Adapter: 0.1-1s, (Quick flash: 50 full power flashes/min)	0.1-1.9 (Quick burst up to 20 flashes/second)
<b>Flash Duration</b>	1/220s - 1/10,000s	1/1,000 – 1/9,000 (max-min power)	1/250 - 1/15,000 sec @ t.1	1/11,000s - 1/1,000s (1/19,000s - 1/1,000s Freeze Mode)
<b>Power Range</b>	9 F-Stops	7 F-Stops	8 F-Stops	9 F-stops (2-500Ws)
<b>Modeling Lamp</b>	10W LED	10W LED	4.5 W LED	20W LED
<b>High-Speed Sync</b>	Yes	Yes	Yes	Yes
<b>Battery Life</b>	Approx. 500 Full Powered Flashes	Approx. 350 Full Powered Flashes	Approx. 400 Full Powered Flashes	Up to 220 full power flashes
<b>Recharge Times</b>	4 Hours	3 Hours	5 Hours	2 Hours
<b>Wireless Remote Triggering</b>	Built-in PIXAPRO PRO STIII Receiver TTL Canon/Nikon - 2.4GHz Remote	Built-in Receiver Optional Interfit TTL-Canon/Nikon 2.4 GHz Remote	Odin-C, Odin-N, Strato II, Opt-Slave, RX OFF (Can only be fired via 3.5mm sync port)	Profoto AirTTL Trigger System Canon/Nikon
<b>Colour Temperature</b>	5600±200k	5700K +/- 100K	5500±200K	Unknown
<b>Dimension</b>	220mm x 245mm x 125mm	34 x 23 x 13cm	140mm x 267mm x 190mm	140mm x 310mm x 210m
<b>Weight</b>	2.66kg	2.85kg	2.1kg	3kg (Including Battery)
<b>Price</b>	Launch Offer £600.00 Including TTL Trigger.* (Regular Price-£699.99)	Around £799.99	Around £930.00	Around 1632.00

\*EssentialPhoto and PIXAPRO® reserve the right to remove the launch offer on the CITI600 TTL at any time without notice.